

RG-RAP6260(H) Reyee Wi-Fi 6 AX6000 High-density Outdoor Omni-directional Access Point



Kode : RG-RAP6260(H)

Kategori : Ruijie & Reyee Wireless

Harga : Rp 4.020.000,00

RG-RAP6260(H) Reyee Wi-Fi 6 AX6000 High-density Outdoor Omni-directional Access Point. With a revolutionary combination of OFDMA and 1024QAM, the latest 802.11ax standard, the 160MHz band and 2.5GE Port (Support PoE In). With gigabit SFP port, the device supports up to 20km transmission from datacenter with single mode fiber.

***Belum termasuk adaptor dan poe injector**

Penawaran Harga Spesial

 **08112039555**

- Ultra-fast 5.95Gbps outdoor AP, best-in-class Wi-Fi performance
- Boost your Internet speed with 2.5GE uplink
- Easily expand extra outdoor Wi-Fi with Reyee Mesh.
- Extra-distance access point deployment with SFP port
- IP68 protection, rock-solid in harsh environments



Specification

Model	RG-RAP6260(H)
Protocol	Wi-Fi 6 (IEEE 802.11ax) Wi-Fi 5 (IEEE 802.11ac Wave 2) Wi-Fi 4 (IEEE 802.11n) IEEE 802.11a, IEEE 802.11b/g
Operating Bands	802.11b/g/n/ac/ax : 2.400GHz ~ 2.4835GHz 802.11a/n/ac/ax: 5.150 - 5.350GHz, 5470 - 5.725GHz, 5.725 - 5850GHz (country specific)
Antenna	Built-In Omnidirectional (2.4GHz: 3dBi, 5GHz: 4dBi)
Spatial Streams	2.4 GHz: 4x4 MU-MIMO 5 GHz: 4x4 MU-MIMO
Max Throughput	Up to 1148 Mbps at 2.4 GHz Up to 4804 Mbps at 5 GHz
Service Ports	1x 100/1000/2500 Base-T ethernet port support PoE IN; 1x 1GBase-X SFP Port 1x DC Port 1x Reset button
Power Supply	IEEE 802.3bt PoE, DC 48V/1A
Power Consumption	≤ 40 W
Operating temperature	-40°C - 65°C
Storage temperature	-40°C - 85°C

MTBF	>400000H
Maximum number of clients	512
Recommended number of clients	130
Maximum Number of SSIDs	8

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1024/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com