

# Teltonika TSW100 Industrial Unmanaged PoE+ Switch




**Kode** : TSW100  
**Kategori** : Teltonika  
**Harga** : Rp 1.545.000,00

TSW100 is an unmanaged Gigabit Ethernet switch supporting Power-over-Ethernet. Classified as power source equipment (PSE), it centralizes the power supply, providing up to 30 watts per port and reducing installation effort. Five Gigabit Ethernet ports provide an economical high-bandwidth solution for a secure industrial Ethernet network.

**Produk ini belum termasuk power adaptor**

Penawaran Harga Spesial

 08112039555

## Features :

- 4 x PoE+ ports with 802.3af and 802.3at support
- Total power budget at PSE up to 120 W
- 5 x Gigabit Ethernet with speeds up to 1000 Mbps
- DIN rail and surface mounting options



## Specification

|                                    |   |
|------------------------------------|---|
| <b>Model</b>                       | TSW100  |
| <b>ETHERNET</b>                    |   |
| <b>LAN</b>                         | 5 x ETH ports, 10/100/1000 Mbps, supports auto MDI/MDIX crossover |
| <b>IEEE 802.3 series standards</b> | 802.3i, 802.3u, 802.3ab, 802.3x, 802.3az, 802.3ad                 |

| POE                             |   |
|---------------------------------|---|
| PoE ports                       | Port 1- 4   |
| PoE standards                   | 802.3af and 802.3at   |
| PoE Max Power per Port (at PSE) | 30 W  |
| PoE Power Budget (at PSE)       | 120 W   |
| PERFORMANCE SPECIFICATIONS      |   |
| Bandwidth (Non-blocking)        | 10 Gbps   |
| Packer buffer                   | 128 KB  |
| MAC address table size          | 2K entries  |
| POWER                           |   |
| Connector                       | 4-pin industrial DC power socket  |
| Input voltage range             | 7 - 57 VDC  |
| Input voltage range for PoE     | 44 - 57 VDC   |
| Power consumption               | Idle: 2 W / Max (no PoE): 9 W / PoE Max: 129 W                            |
| PHYSICAL INTERFACES             |   |
| Ethernet                        | 5 x RJ45 ports, 10/100/1000 Mbps  |
| Status LEDs                     | 1 x Power LED, 10 x LAN status LEDs                                       |
| Power                           | 1 x 4-pin power connector   |
| Other                           | 1 x Grounding screw   |
| PHYSICAL SPECIFICATION          |   |
| Casing material                 | Full aluminum housing   |
| Dimensions (W x H x D)          | 115 x 32 x 95 mm  |
| Mounting options                | DIN rail or wall mounting (additional kit needed), flat surface placement |
| OPERATING ENVIRONMENT           |   |
| Operating temperature           | -40 °C to 75 °C   |
| Operating humidity              | 10% to 90% non-condensing   |
| Ingress Protection Rating       | IP30  |

Standard Package Contains :

- TSW100
- 62 W PSU
- QSG (Quick Start Guide)
- Packaging box

[Download Datasheet](#)

\* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

**URL :** <https://www.citraweb.com/produk/1062/>

**Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email [sales@citraweb.com](mailto:sales@citraweb.com)**

[www.citraweb.com](http://www.citraweb.com)