CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

RG-RAP2266 REYEE Wi-Fi 6 AX3000 Indoor Ceiling-Mount Access Point



Kode : RG-RAP2266
Brand : Ruijie - Reyee
Jenis : Wireless Indoor
Harga : Rp 2.064.000,00

RG-RAP2266 Ruijie Reyee Wi-Fi AX3000 Dual-band Round Ceiling AP. Installation With Rotating, Quick and Easy.
***Belum termasuk adaptor dan poe injector**
***Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**
Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial
08112039555

Product Highlights :

- Dual-radio performance, gigabit wireless Ceiling-mounted AP
- Capable of Reyee Mesh and 802.11K/V
- Easy installation, rotating and done
- New circular aesthetics, more in line with the hotel decoration stylex
- Powerful Standalone Portal via Ruijie Cloud





Specification

Model	RG-RAP2266

www.citraweb.com

CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

Wi-Fi Standards	Wi-Fi6 (IEEE 802.11ax) Wi-Fi5 (IEEE 802.11ac Wave 2) Wi-Fi4(IEEE 802.11n) IEEE 802.11a IEEE 802.11b/g
MIMO	2.4GHz?2×2 ,MU-MIMO 5GHz?2×2 ,MU-MIMO
Max. Wi-Fi Speed	2.4GHz: 574Mbps 5GHz: 2402Mbps
Antenna	5
Antenna Type	Built-In Omnidirectional
Antenna Gain	2.4 GHz:3.53dBi 5 GHz:5.15dBi Note The peak gain mentioned above refers to the gain of a single antenna.
Transmit Power	EIRP: ≤31dBm (2.4GHz) ≤32.7dBm (5GHz) Country-specific restrictions apply
Fixed Ports	1×10/100/1000 Base-T port 1xDC port 1×Reset button
Max. Clients	512
Recommended Clients	110
Max. SSIDs	8
Recommended Wi-Fi Coverage Radius	2.4GHz: 40 meters 5GHz: 70 meters The Wi-Fi coverage is related to the installation environment of the access point
Max. Wi-Fi Coverage Radius	150 meters
Operation Frequency Bands	802.11b/g/n/ax: 2.400 GHz to 2.4835 GHz 802.11a/n/ac/ax:5.150 GHz to 5.350 GHz, 5.470 GHz to 5.725 GHz , 5.725 GHz to 5.850 GHz country-specific restrictions apply
Frequency Bandwidth	2.4 GHz: Auto/20/40 MHz 5 GHz: Auto/20/40/80/160 MHz
Roaming	Layer 2 roaming Layer 3 roaming
Security Mode	WPA-PSK, WPA2-PSK, WPA/WPA2-PSK;
Network Access Mode	PPPoE Client DHCP Client Static IP

www.citraweb.com

Dimensions	220 mm x 220 mm x 52.6 mm (8.66 in. x 8.66 in. x 2.07 in., without the mounting bracket)
Installation	Ceiling-Mountable
Power Supplies	IEEE 802.3at PoE DC 12V/2A
Power Consumption	≤ 18W
Operating Temperature	0°C to 40°C
Storage Temperature	-40°C to 70°C
Operating Humidity	5% to 95% Noncondensing
Storage Humidity	5% to 95% Noncondensing
Port Surge	+/-2kV
MTBF	>400000H

Download Datasheet

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1067/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com