


Access Point GWN7625



Kode : GWN7625
Kategori : Grandstream
Harga : Rp 1.472.000,00

The GWN7625 is an 802.11ac Wave-2 Wi-Fi access point ideal for small-to-medium sized businesses, offers 4x4:4 MU-MIMO technology on the 5G band and 2x2:2 MU-MIMO on the 2.4G band.

Penawaran Harga Spesial

 08112039555

- 2.03 Gbps wireless throughput and 2 Gigabit wireline ports 5GHz 4x4:4 MU-MIMO
- Supports up to 200 concurrent Wi-Fi client devices
- Advanced QoS to ensure real-time performance of low-latency applications
- Anti-hacking secure boot and critical data/control lockdown via digital signatures, unique security certificate/random default password per device
- Self power adaptation upon auto detection of PoE or PoE+
- Embedded controller can manage up to 30 local GWN series APs;
- GWN.Cloud offers unlimited AP management; GWN Manager offers premise based software controller

Spesifikasi

Model	GWN7625
Wi-Fi Standards	IEEE 802.11 a/b/g/n/ac (Wave-2)
Antennas	6 single frequency internal antennas 2.4GHz, gain 3.5dBi 5GHz, gain 4.5dBi
Wi-Fi Data Rates	2.4G: IEEE 802.11n: 6.5Mbps to 300Mbps IEEE 802.11b: 1, 2, 5.5, 11 Mbps IEEE 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 5G: IEEE 802.11ac: 6.5 Mbps to 1733 Mbps IEEE 802.11n: 6.5Mbps to 600Mbps IEEE 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps <i>*Actual throughput may vary depending on many factors including environmental conditions, distance between devices, radio interference in the operating environment and mix of devices in the network</i>
Frequency Bands	2.4GHz Radio: 2412 - 2484 MHz 5GHz Radio: 5180 - 5825 MHz <i>*Not all frequency bands can be used in all regions</i>
Channel Bandwidth	2.4G: 20 and 40 MHz 5G: 20,40 and 80 MHz
Wi-Fi and System Security	WEP, WPA/WPA2-PSK, WPA/WPA2 Enterprise (TKIP/AES); WPA3, anti-hacking secure boot and critical data/control lockdown via digital signatures, unique security certificate and random default password per device
MIMO	2x2:2 2.4GHz(MIMO) 4x4:4 5GHz(MU-MIMO)
Maximum TX Power	2.4G: 23dBm 5G: 25dBm <i>*Maximum power varies by country, frequency band and MCS rate</i>

Receiver Sensitivity	2.4G 802.11b: -96dBm@1Mbps, -88dBm@11Mbps; 802.11g: -93dBm @6Mbps, -75dBm@54Mbps; 802.11n 20MHz: -73dBm @MCS7; 802.11n 40MHz:-70dBm @MCS7 5G 802.11a: -92dBm @6Mbps, -74dBm @54Mbps; 802.11n 20MHz: -74dBm @MCS7; 802.11n 40MHz:-71dBm @MCS7 802.11ac 20MHz: -67dBm@MCS8; 802.11ac: HT40:- 63dBm @MCS9; 802.11ac 80MHz: -59dBm @MCS9	
SSIDs	16 SSIDs total, 8 per radio (2.4GHz & 5GHz)	
Concurrent Clients	200	Network Interfaces 2x autosensing 10/100/1000 Base-T Ethernet Ports
Auxiliary Ports	1x Reset Pinhole, 1x Kensington lock	
Mounting	Indoor wall mount or ceiling mount, kits included	
LEDs	3 tri-color LEDs for device tracking and status indication	Network Protocols IPv4, IPv6, 802.1Q, 802.1p, 802.1x, 802.11e/WMM
Network Management	Embedded controller can manage up to 30 local GWN APs GWN.Cloud offers a free cloud management platform for unlimited GWN APs GWN Manager offers premise-based software controller for up to 3,000 GWN APs	QoS 802.11e/WMM, VLAN, TOS
Power and Green Energy Efficiency	Supports 802.3az PoE 802.3af/ 802.3at; Maximum Power Consumption: <13W	
Environmental	Operation: 0°C to 50°C Storage: -10°C to 60°C Humidity: 10% to 90% Non-condensing	
Physical	Unit Dimension: 205.3mm(L)x205.3mm(W)x45.9mm(H)	
Package Content	GWN7625 802.11ac Wave-2 Wireless AP, Mounting Kits, Quick Installation Guide	
Compliance	FCC, CE, RCM, IC, UKCA	

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1089/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com