

TAP100 TELTONIKA WI-FI Access Point

Kode : TAP100

Brand : Teltonika

Jenis : Wireless Indoor

Harga : Rp 1.048.000,00



TAP100 is the Teltonika Networks Access Point, perfect for strengthening Wi-Fi coverage in small enterprise and commercial spaces. This PoE-in access point can be powered by active PoE devices via its RJ45 port and was designed with simplicity and ease of installation in mind.

***Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**

Penawaran Harga Spesial

 08112039555

Features :

- Can be powered by PoE devices via RJ45 port
- UV-stabilized plastic housing that blends in with its environment
- Integrated mounting bracket for easy ceiling setup
- Free access to RMS Management for 24 months



Specification

Model	TAP100
WIRELESS	
Wireless mode	IEEE 802.11b/g/n (Wi-Fi 4)
Wi-Fi security	WPA2-EAP/WPA3-EAP Mixed Mode, WPA3-EAP, WPA2-PSK/WPA3-SAE Mixed Mode, WPA3-SAE, OWE, WPA-PSK/WPA2-PSK Mixed Mode, WPA2-PSK, WPA2-EAP; AES-CCMP, TKIP, Auto Cipher modes, client separation
SSID/ESSID	SSID stealth mode and access control based on MAC address
Wi-Fi users	Up to 100 simultaneous connections
Wireless mesh/roaming	Fast roaming (802.11r)
Wireless MAC filter	Whitelist, blacklist
ETHERNET	
Ethernet	1 x RJ45 port 10/100 Mbps, compliance with IEEE 802.3, IEEE 802.3u, 802.3az standards, supports auto MDI/MDIX crossover
NETWORK	
Network protocols	TCP, UDP, IPv4, IPv6, ICMP, HTTP, HTTPS, SSL v3, TLS, ARP, SSH, DHCP client, SMNP
SECURITY	
Authentication	Pre-shared key, digital certificates, X.509 certificates, TACACS+, Radius, IP & Login attempts block
VLAN	Tag-based VLAN separation
MONITORING & MANAGEMENT	
WEB UI	HTTP/HTTPS, status, configuration, FW update, CLI, troubleshoot, event log, system log, kernel log
FOTA	Firmware update from server, automatic notification
SSH	SSH (v1, v2)
SNMP	SNMP (v1, v2, v3), SNMP Trap
JSON-RPC	Management API over HTTP/HTTPS
RMS	Teltonika Remote Management System (RMS)

CHARACTERISTICS	
CPU	Mediatek, 580 MHz, MIPS 24KEc
RAM	64 MB
FLASH storage	16 MB
Connector	RJ45 Socket
Input voltage range	44.0 - 57.0 V
PoE standards	802.3af PoE Class 1
Power consumption	< 2 W Max
Ethernet	1 x RJ45 ports, 10/100 Mbps
Status LEDs	1 x Power LED (can be turned off from web-UI)
Antennas	2 x Internal for 2.4 GHz Wi-Fi
Reset	Reboot/User default reset/Factory reset button
FIRMWARE CUSTOMIZATION	
Operating system	RutOS (OpenWrt based Linux OS)
Supported languages	Busybox shell, Lua, C, C++
Development tools	SDK package with build environment provided
PHYSICAL SPECIFICATION	
Casing material	UV stabilized plastic
Dimensions (W x H x D)	158 mm x 30 mm
Mounting options	AP Mounting Bracket (for ceiling mount)
Operating temperature	-40 °C to 75 °C
Ingress Protection Rating	IP30
Operating humidity	10% to 90% non-condensing
REGULATORY & TYPE APPROVALS	
Regulatory	CE, UKCA, CB, FCC, IC, WEEE, ANRT
SAFETY	

Standards	IEC 62368-1:2018 EN IEC 62368-1:2020+A11:2020 EN IEC 62311:2020
------------------	---

Standard package :

- TAP100 Access point
- 15 W PoE Injector
- QSG (Quick Start Guide)
- Packaging box

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1119/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com