

# Cambium Networks ePMP Force 300-25L



**Kode** : ePMP-Force-300-25L

**Brand** : Cambium

**Jenis** : Wireless Outdoor

**Harga** : Rp 2.150.000,00

Rp 2.535.000,00

Cambium Networks ePMP™ Force 300-25L dirancang untuk beroperasi pada jaringan dengan tingkat interferensi tinggi namun tetap dapat memberikan throughput superior hingga lebih dari 400 Mbps. Dilengkapi dengan integrated antenna dish dengan gain lebih tinggi mencapai 25 dBi.

Penawaran Harga Spesial

08112039555

Force L Series Quick Look:

- High-performance subscriber modules for PTP and PMP fixed wireless broadband applications
- Up to 400 Mbps capacity leveraging proven ePMP platform on 802.11ac models (200 Mbps on 802.11n models)
- Compatible with all ePMP Access Points, including ePMP 3000 and ePMP 3000L
- 3-year hardware warranty

## SPECTRUM

Channel Spacing	Configurable in 5 MHz increments
Frequency Range	Wide Band Operation 4910–6200 MHz (Allowable frequencies and bands are dictated by individual country regulations)
Channel Width MHz	20   40   80
Ethernet Interface	10/100/1000 BaseT, compatible with Cambium PoE & standard PoE pinouts

## PERFORMANCE

Nominal Receive Sensitivity (w/FEC) @20 MHz Channel	MCS0 = -89 dBm; MCS9 = -62 dBm
Nominal Receive Sensitivity (w/FEC) @40 MHz Channel	MCS0 = -86 dBm; MCS9 = -60dBm
Nominal Receive Sensitivity (w/FEC) @80 MHz Channel	MCS0 = -84 dBm to MCS9 = -57 dBm

## PHYSICAL

Environmental	IP55
Temperature	-30°C to 60°C (-22°F to 140°F)
Weight	1.6 kg (3.5 lbs)
Dimensions	280 x 470 x 470 mm (11.0 x 18.5 x 18.5 in.)

**SECURITY**

Encryption	128-bit AES (CCMP mode)
------------	-------------------------

**ANTENNA SPECIFICATIONS**

Frequency Range	4.920-6.400 MHz
Antenna Type	Integrated Dish
Peak Gain	25 dBi
3 dB Beamwidth Azimuth	6° to 10°
3 dB Beamwidth Elevation	6° to 10°
Front-to-Back Isolation	25 dB
Cross Polarization	20 dB

**Download Data Sheet :** [Data Sheet ePMP Force L Series](#)

Rencanakan dan kelola penerapan ePMP Force 300-25L Anda dengan **LINKPlanner** dan **cnMaestro™**





\* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

**URL :** <https://www.citraweb.com/produk/1149/>

**Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email [sales@citraweb.com](mailto:sales@citraweb.com)**