

FD1601S-B1 1PON 2GE 1SFP+ GPON OLT



Kode : FD1601S-B1
Kategori : C-DATA & PON Accessories
Harga : Rp 4.300.000,00

GPON OLT FD1601S-B1 completely meet relative standard of ITU G.984.x and FSAN, the device with 2 uplink Ethernet ports and 1 10 Gigabit uplink port and 1 GPON port. Each GPON port supports the splitting ratio of 1:128, The GPON system supports up to 128 terminal connections.

Penawaran Harga Spesial

08112039555

Specification

Model	FD1601S-B1
Uplink Port	2 x 10/100/1000M auto-negotiation Ethernet ports
Optional Port	10 Gigabit uplink port
PON Port	Quantity : 1
	Physical interface : SFP slot
	Interface type : GPON: ITU-TG.984.2 Class B+/Class C+
	Max splitting ratio : GPON: 1:128
Management Port	1 CONSOLE local management port
Transmission distance	20KM
Port rate	GPON: Downstream: 2.5Gbps Upstream: 1.25Gbps
Wavelength	Forwarding: 1490nm Receiving: 1310nm
Interface type	SC/UPC
Fiber type	9/125µm SMF (Single Mode Fiber)
Light transmission power	Class B+ +1.5 ~ +5dBm
	Class C+ +3 ~ +7dBm
Receiving sensitivity	Class B+ : -28dBm
	Class C+ : -30dBm
Saturation power	Class B+ -8dBm
	Class C+ -12dBm
Backplane Bandwidth	27.75G
Power supply	AC : 100V ~ 240V, 47~63Hz
	DC : External adapter mode 12V/2.5A

Working temperature	-15 ~ 50 C
Storage temperature	-40 ~ 85 C
Ambient humidity	5 ~ 90% (Non-condensing)

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1228/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com