

FD1601S-B1 C-DATA 1PON 2GE 1SFP+ GPON OLT

Kode : FD1601S-B1
Brand : C-Data
Jenis : FTTH OLT
Harga : Rp 3.249.999,00
 Rp 4.300.000,00



GPON OLT FD1601S-B1 CDATA completely meet relative standard of ITU G.984.x and FSAN, the device with 2 uplink Ethernet ports and 1 10 Gigabit uplink port and 1 GPON port. Each GPON port supports the splitting ratio of 1:128, The GPON system supports up to 128 terminal connections.

Penawaran Harga Spesial
 **08112039555**

Specification

| | |
|---------------------------------|---|
| Model | FD1601S-B1 |
| Uplink Port | 2 x 10/100/1000M auto-negotiation Ethernet ports |
| Optional Port | 10 Gigabit uplink port |
| PON Port | Quantity : 1 |
| | Physical interface : SFP slot |
| | Interface type : GPON: ITU-TG.984.2 Class B+/Class C+ |
| | Max splitting ratio : GPON: 1:128 |
| Management Port | 1 CONSOLE local management port |
| Transmission distance | 20KM |
| Port rate | GPON: Downstream: 2.5Gbps Upstream: 1.25Gbps |
| Wavelength | Forwarding: 1490nm Receiving: 1310nm |
| Interface type | SC/UPC |
| Fiber type | 9/125µm SMF (Single Mode Fiber) |
| Light transmission power | Class B+ +1.5 ~ +5dBm Class C+ +3 ~ +7dBm |

| | |
|------------------------------|--|
| Receiving sensitivity | Class B+ : -28dBm Class C+ : -30dBm |
| Saturation power | Class B+ -8dBm Class C+ -12dBm |
| Backplane Bandwidth | 27.75G |
| Power supply | AC : 100V ~ 240V, 47~63Hz DC : External adapter mode 12V/2.5A |
| Working temperature | -15 ~ 50 C |
| Storage temperature | -40 ~ 85 C |
| Ambient humidity | 5 ~ 90% (Non-condensing) |

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1228/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com