CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

RG-RAP72Pro REYEE Wi-Fi 7 BE5040 Dual-Band Ceiling Access Point

Kode : RG-RAP72Pro
Brand : Ruijie - Reyee
Jenis : Wireless Indoor

RG-RAP72Pro Ruijie Reyee Wi-Fi 7 BE5040 Dual-Band Ceiling Access Point.

***Belum termasuk adaptor dan poe injector**
***Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**
Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial
08112039555

Product Highlights :

- Next-generation performance with Wi-Fi 7, delivering extra-high wireless speeds
- Superior streaming with Wi-Fi 7's exclusive MLO feature
- Compact design and easy installation
- Enhanced data transmission with 4K-QAM for faster speeds
- Ideal for integrating with enterprise switches to create a robust office network



Specification

Model	RG-RAP72Pro

www.citraweb.com

CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

Wi-Fi Standards	Wi-Fi 4: IEEE 802.11a/b/g/n Wi-Fi 5: IEEE 802.11ac Wave 2 Wi-Fi 6: IEEE 802.11ax Wi-Fi 7: IEEE 802.11be
Spatial Streams	2.4GHz, 2×2 MU-MIMO 5GHz, 3×3 MU-MIMO
Data Rate	Max. throughput: 5011Mbps 2.4 GHz: 688Mbps 5 GHz: 4323Mbps
Antenna	Built-in Antenna gain: 2.4 GHz, 2.0 dBi; 5 GHz, 3 dBi
Channel Width	2.4 GHz: Auto/20/40 MHz 5 GHz: Auto/20/40/80/160 MHz
Transmit Power	2400-2483.5 MHz, EIRP ≤ 27 dBm 5150-5350 MHz, EIRP ≤ 23 dBm 5725-5825 MHz, EIRP ≤ 23 dBm
Service Ports	1 x 10/100/1000BASE-T port 1 x 10/100/1000/2500BASE-T port
Max. Clients	512
Recommended Clients	110
Max. SSIDs	8
Operating Mode	AP mode and router mode
Dimensions	208mm x 208mm x 40mm (8.19in. x 8.19in. x 1.57in.)(excluding the mounting bracket)
Installation	Ceiling-mount or wall-mount
Power Supplies	IEEE 802.3at standard PoE or DC (12 V, 2.5 A)power supply
Power Consumption	≤ 30W
Operating Temperature	0°C to 40°C
Storage Temperature	-40°C to 70°C
Operating Humidity	5% to 95% Noncondensing
Storage Humidity	5% to 95% Noncondensing
Surge Protection	+/-2kV
MTBF	>400000H

Download Datasheet

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

www.citraweb.com

CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

URL : https://www.citraweb.com/produk/1272/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com