

# V1601E02-DP V-SOL 2PON EPON OLT

**Kode** : V1601E02-DP

**Brand** : V-Sol

**Jenis** : FTTH OLT

**Harga** : Rp 4.000.000,00

Rp 4.300.000,00



V1601E02-DP vsol is a compact and cost-effective EPON OLT product. It supports functionalities such as STP/RSTP/MSTP, IGMP Snooping, and VLAN Translation/Q-in-Q, ensuring network stability and security. Additionally, it offers features like port mirroring, L3 static routing, RIP/OSPF dynamic routing, and can be efficiently deployed and managed through SNMP/Telnet/CLI/WEB/SSH interfaces.

**2\*EPON, 4\*RJ45+2\*SFP/(SFP+)**
**\*Sudah termasuk 2x SFP 9dBm**

Penawaran Harga Spesial

 **08112039555**


## Specification

|                    |                       |
|--------------------|-----------------------|
| <b>Model</b>       | V1601E02-DP           |
| <b>Uplink Port</b> | QTY : 6               |
|                    | RJ45(1G) : 4          |
|                    | SFP(1G)/SFP+(10G) : 2 |

|                                   |  |
|-----------------------------------|--|
| <b>EPON Port</b>                  | QTY : 2  |
|                                   | Physical Interface : SFP Slots   |
|                                   | Supported PON module level :<br>PX20, PX20+, PX20++, PX20+++, PX20++++     |
|                                   | Max splitting ratio : 1:64   |
| <b>Management Port</b>            | 1*10/100 BASE-T out-band port, 1*CONSOLE port                              |
| <b>Backplane Bandwidth (Gbps)</b> | 128  |
| <b>Port Forwarding Rate(Mpps)</b> | 38.688   |
| <b>PON Port Specification</b>     | Transmission Distance : 20KM   |
|                                   | EPON port speed"Symmetrical 1.25Gbps                                       |
|                                   | Wavelength<br>TX 1490nm<br>RX 1310nm                                       |
|                                   | Connector : SC/UPC   |
|                                   | Fiber Type : 9/125µm SMF   |
| <b>Power supply</b>               | AC : Working Voltage Range: 100~240V, Rated Voltage: 110V/220V<br>DC : 48V |
| <b>Management Mode</b>            | SNMP/Telnet/CLI/WEB/SSH v2   |
| <b>Working temperature</b>        | -20 ~ +60 C  |
| <b>Storage temperature</b>        | -40 ~ +70 C  |
| <b>Relative Humidity</b>          | 5 ~ 95% (Non-condensing)   |
| <b>Dimension (L*W*H)</b>          | 442 x 200 x 43.6 mm  |

[Download Datasheet](#)

\* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

**URL :** <https://www.citraweb.com/produk/1293/>

**Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email [sales@citraweb.com](mailto:sales@citraweb.com)**