CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

V1600D4-BT V-SOL 4PON EPON OLT

Kode : V1600D4-BT
Brand : V-Sol
Jenis : FTTH OLT
Harga : Rp 5.500.000,00
~~Rp 6.000.000,00~~

V1600D4-BT vsol provides 4GE(copper) and 4*SFP/SFP+ slots independent interface for uplink, and 4*EPON OLT ports for downlink. It can support overall 256 ONU's with 64 ONU's per PON port.

4*EPON,4GE(RJ45)+4*10GE(SFP+) Dual power modules available in DC/AC

*Sudah termasuk 4x SFP 9dBm

Penawaran Harga Spesial
08112039555

SUPPORT BBU*
Stable working, non-stop power OLT

DC out
14.4-15V, ≥4A

AC 90~264V,
47/63Hz

Wind Power

DC in
12V/0.5A

BATTERY

INVERTER

Control/Inverter

DC 12V/0.5A

Solar Panel

* V1600D4-BT Support BBU(Battery Back-Up Unit)
Charging : Constant current mode, DC 12V/0.5A.
BBU Full voltage Output: DC 14.4-15V, ≥4A

Specification

CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

Model	V1600D4-BT
Uplink Port	QTY : 8
	RJ45(1G) : 4
	SFP(1G)/SFP+(10G) : 4
EPON Port	QTY : 4
	Physical Interface : SFP Slots
	Supported PON module level : PX20, PX20+, PX20++, PX20+++
	Max splitting ratio : 1:64
Management Port	1*10/100 BASE-T out-band port, 1*CONSOLE port
Backplane Bandwidth (Gbps)	128
Port Forwarding Rate(Mpps)	71.424
PON Port Specification	Transmission Distance : 20KM
	EPON port speed"Symmetrical 1.25Gbps
	Wavelength TX 1490nm RX 1310nm
	Connector : SC/UPC
	Fiber Type : 9/125µm SMF
Power supply	AC 100~240 V, 50/60 Hz DC: 12V
Management Mode	SNMP/Telnet/CLI/WEB/SSH v2
Working temperature	-20 ~ +60 C
Storage temperature	-40 ~ +70 C
Relative Humidity	5 ~ 95% (Non-condensing)
Dimension (L*W*H)	442 x 200 x 43.6 mm

Download Datasheet

* *Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1296/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com