

# V2802DAC V-SOL 1XPON 2GE DUAL BAND WIFI5 ONU



**Kode** : V2802DAC

**Brand** : V-Sol

**Jenis** : FTTH ONT/ONU/MDU

**Harga** :

1 - 19 : Rp 420.000,00

20 - ... : Rp 335.000,00

V2802DAC vsol (2GE+WiFi5 XPON ONT) is designed to meet the FTTH requirements of fixed network operators. The ONT is based on a high-performance chipset (Realtek) technology solution, supporting IEEE802.11b/g/n/ac WIFI technology and other Layer 2/Layer 3 functions. The ONT supports the OAM/OMCI protocol, and we can configure or manage various services of the ONT on the VSOL OLT.

## 2\*GE+WiFi5

**\*Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**

Penawaran Harga Spesial

 08112039555

## Key Features :

- Detect and exchange PON mode automatically
- Support EasyMesh protocol
- WiFi5 Dual Band 1200Mbps
- IPv4/IPv6 Stack

## Specification

<b>Model</b>	V2802DAC
<b>PON Interface</b>	1XPON port(EPON PX20+ and GPON Class B+) SC single mode, SC/UPC connector TX optical power: 0~+4dBm RX sensitivity: -27dBm Overload optical power: -3dBm(EPON) or -8dBm(GPON) Transmission distance: 20KM Wavelength: TX 1310nm, RX1490nm
<b>Wifi Interface</b>	Compliant with IEEE802.11b/g/n/ac WiFi : 2.4GHz 2x2, 5.8GHz 2x2, 5dBi antenna, rate up to 1.167Gbps Multiple SSID TX power: 2.4GHz: 23dBm; 5GHz: 24dBm RX power: 2.4GHz: HT40-MCS7 -72dBm; 5GHz: VHT80 MCS9 <-62dBm

<b>User interface</b>	2×GE, Auto-negotiation, RJ45 ports
<b>O&amp;M</b>	OAM/OMCI, Telnet, WEB, TR069 Support full management of HGU functions by VSOL OLT
<b>Connect Mode</b>	Support bridge, router & bridge/router mixed mode
<b>QoS</b>	Support 4 queues Support SP, WRR, 802.1P and DSCP
<b>Data Service Functions</b>	<ul style="list-style-type: none"> <li>• Full speed non-blocking switching</li> <li>• 2K MAC address table</li> <li>• 8 full range VLAN ID</li> <li>• Support VLAN tag, untag, transparent, trunk, translation mode</li> <li>• Integrated port monitoring, port mirroring, port rate limiting, port SLA, etc</li> <li>• Support auto polarity detection of Ethernet ports (AUTO MDIX)</li> <li>• Support IGMP v1/v2/v3 snooping/proxy and MLD v1/v2 snooping/proxy</li> </ul>
<b>Wireless</b>	<ul style="list-style-type: none"> <li>• Integrated 802.11b/g/n/ac</li> <li>• Authentication : WEP/WAP-PSK(TKIP)/WAP2-PSK(AES)</li> <li>• Modulation type : DSSS, CCK and OFDM</li> <li>• Encoding scheme : BPSK, QPSK, 16QAM and 64QAM</li> <li>• Easymesh</li> </ul>
<b>L3</b>	<ul style="list-style-type: none"> <li>• IPv4, IPv6 and IPv4/IPv6 dual stack</li> <li>• DHCP/PPPOE/Static</li> <li>• Static route, DHCP Server</li> <li>• NAT/DMZ/DDNS/Virtual Server</li> </ul>
<b>Security</b>	<ul style="list-style-type: none"> <li>• Support Firewall</li> <li>• Support Mac filter Based on MAC or URL</li> <li>• Support ACL</li> </ul>
<b>Dimension</b>	178mm×120mm×30mm(L×W×H)
<b>Power adapter</b>	DC 12V, 1.0A, external AC-DC power adaptor
<b>Power supply</b>	≤12W
<b>Operating condition</b>	Operating temp : -10 ~ +55C Operating humidity : 5 ~ 95% (non-condensing)
<b>Storing condition</b>	Storing temp: -40 ~ +70C Storing humidity: 5 ~ 95% (non-condensing)
<b>Indicators</b>	PWR, PON, LOS, WAN, LAN1, LAN2, 2.4G, 5G

[Download Datasheet](#)

\* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

**URL :** <https://www.citraweb.com/produk/1298/>

**Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email [sales@citraweb.com](mailto:sales@citraweb.com)**