

FD1604E-C1 C-DATA 4PON Expandable GPON OLT

Kode : FD1604E-C1

Brand : C-Data

Jenis : FTTH OLT

Harga : Rp 9.000.000,00

Rp 9.700.000,00



GPON OLT FD1604E-C1 completely meets relative standard of ITU-T G.984.x/G.988, which is 1U rack-mounted device with 1 USB interface, 4 uplink GE ports, 4 uplink SFP ports, 2 10GE uplink ports. FD1604E-C1 has 4 fixed GPON ports and 1 4 GPON port service card (optional). Each GPON port supports the splitting ratio of 1:128.

***FD6041T (4 PON Optional Module)**

Penawaran Harga Spesial

 08112039555



Specification

Model	FD1604E-C1
Uplink Port	Combo Port : 4* 10/100/1000M auto-negotiation Ethernet ports 4* SFP interfaces 10-Gigabit : 2* SFP+ interfaces
PON Port	4* GPON / 8* GPON (Optional with FD6041T 4 PON Optional Module) Physical interface : SFP slot Interface type : ITU-TG.984.2 Class B+/Class C+/Class C++ Max splitting ratio : GPON: 1:128
Management Port	1* 100/1000BASE-Tx out-band Ethernet port 1* CONSOLE local management port
USB Port	1* USB interface (It's used to backup configuration, upgrade program and record log information)
Transmission distance	20KM
Port rate	GPON: Downstream: 2.5Gbps Upstream: 1.25Gbps
Wavelength	Forwarding: 1490nm Receiving: 1310nm
Interface type	SC/UPC
Fiber type	9/125µm SMF (Single Mode Fiber)
Light transmission power	Class B+ : +1.5 ~ +5dBm Class C+ : +3 ~ +7dBm Class C++ : +4.5 ~ +10dBm
Receiving sensitivity	Class B+ : -28dBm Class C+ : -30dBm Class C++ : -31dBm
Saturation power	Class B+ : -8dBm Class C+ : -12dBm Class C++ : -10dBm
Backplane Bandwidth	78G
Power supply	AC : 100V ~ 240V 1.8A, 50/60Hz
Maximum Power	49W
Working temperature	-15 ~ 50 C
Storage temperature	-40 ~ 85 C
Ambient humidity	5 ~ 90% (Non-condensing)

[Download Datasheet](#)

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : <https://www.citraweb.com/produk/1424/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com