

eKitEngine AP771 HUAWEI 3570 Mbps Dual-Band Omnidirectional Outdoor Wi-Fi 7 Access Point

**Kode** : AP771**Brand** : Huawei**Jenis** : Wireless Outdoor**Harga** : Rp 3.604.000,00

HUAWEI eKitEngine AP771 3570 Mbps Dual-Band Omnidirectional Outdoor Wi-Fi 7 Access Point adalah *Access Point outdoor* berteknologi **Wi-Fi 7** (802.11be) yang dirancang khusus untuk memberikan jangkauan nirkabel optimal di area terbuka. Memiliki perlindungan terhadap air dan debu bersertifikasi IP65 serta ketahanan terhadap lonjakan listrik (*surge protection*), AP ini menghadirkan kecepatan dan stabilitas sinyal berstandar Wi-Fi 7 yang ideal untuk area publik berdensitas tinggi seperti alun-alun, jalan pejalan kaki, dan taman hiburan.

***Belum termasuk adaptor dan poe injector**

***Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial **08112039555**

- **Outdoor AP**
- **Wi-Fi 7**
- **3.57 Gbps device rate**
- **Dual-radio**
- **130 access users recommended**
- **Max. 256 access users**
- **28 dBm transmit power**
- **130 m optimal coverage distance**
- **Omnidirectional antenna**



Spesifikasi

Model	AP771
Wi-Fi standard	2.4 GHz: 802.11b/g/n/ax/be 5 GHz: 802.11a/n/ac/ac Wave 2/ax/be
Radio interface	Built-in omnidirectional antennas
Antenna gain	2.4 GHz: 4 dBi/chain (peak value) 2 dBi (combined gain) 5 GHz: 7 dBi/chain (peak value) 4 dBi (combined gain)
Maximum transmit power	2.4 GHz: 25 dBm/chain 28 dBm (combined power) 5 GHz: 24 dBm/chain 27 dBm (combined power)
MIMO spatial streams	Radio 0 (2.4 GHz): 2x2 Radio 1 (5 GHz): 2x2
Operating frequency band	2.4GHz,5GHz
Maximum channel bandwidth [MHz]	Radio 0 (2.4 GHz): 40 MHz Radio 1 (5 GHz): 160 MHz
Optimal Signal Distance (m)	130
Max Number of Access Users	256
Recommended Number of Access Users	130
Device Rate	3.57 Gbps
Power supply mode	PoE
Rated input voltage [V]	PoE: 802.3at/af
Input voltage range [V]	PoE: 802.3at/af

Maximum number of physical ports on the entire device	1x 2.5GE (RJ45) 100M/1000M/2.5G auto-sensing
Radio number	2
Dimensions without packaging (H x W x D) [mm(in.)]	270 mm x 196 mm x 51 mm (10.63 in. x 7.72 in. x 2.01 in.)
Long-term operating temperature [°C(°F)]	-30°C to +60°C (-22°F to +140°F) (From 1800 m to 5000 m [5905.51 ft. to 16404.20 ft.], the maximum ambient temperature decreases by 1°C [1.8°F] for every 300 m [984.25 ft.] increase in altitude.)
Long-term operating relative humidity [RH]	Operating humidity: 5% RH to 95% RH Storage humidity: 5% RH to 95% RH (non-condensing)
Ingress protection level (dustproof/waterproof)	IP65

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1547/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com