CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

TP-LINK EAP110-Outdoor OMADA 300Mbps Wireless N Outdoor Access Point



Kode : EAP110-Outdoor
Brand : TP-Link Omada
Jenis : Wireless Indoor
Harga : Rp 567.000,00

TP-LINK EAP110-Outdoor OMADA merupakan perangkat access point outdoor dengan teknologi **2×2 MIMO** 2.4GHz up to 300 Mbps. Dilengkapi dengan 1 port Fast Ethernet (Support Passive PoE).

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

***Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**

Penawaran Harga Spesial
08112039555

- **Ideal untuk Lingkungan Luar Ruangan** : Casing tahan cuaca IP65 untuk aplikasi Wi-Fi luar ruangan.
- **Wi-Fi Cepat** : Hingga 300Mbps Wi-Fi dengan 2×2 MIMO.
- **Jangkauan Jauh** : Penguat daya tinggi khusus dan antena profesional.
- **Terintegrasi ke dalam Omada SDN** : Zero-Touch Provisioning (ZTP), Manajemen Cloud Terpusat, dan Pemantauan Cerdas.
- **Manajemen Terpusat** : Akses cloud dan aplikasi Omada untuk kenyamanan maksimal dan manajemen yang mudah.
- **Dukungan PoE** : Mendukung PoE Pasif (adaptor PoE disertakan) untuk kemudahan pemasangan.
- **Jaringan Tamu Aman** : Dilengkapi dengan berbagai pilihan otentikasi (SMS/Facebook Wi-Fi/Voucher, dll.) dan teknologi keamanan nirkabel yang melimpah.

www.citraweb.com



Spesifikasi

Model	EAP110-Outdoor
HARDWARE FEATURES	
Interface	1× Port Fast Ethernet (RJ-45) (Mendukung PoE Pasif)
Button	Reset
Power Supply	PoE Pasif 24V (+4,5 pin; -7,8 pin. Adaptor PoE disertakan)
Max. Power Consumption	3,12 W
Dimensions (W x D x H)	8,5 × 1,8 × 1,1 inci (216 × 46 × 27 mm)
Antenna	2× 3 dBi Eksternal Omni tahan air
Weatherproof Enclosure	IP65
Mounting	Pemasangan pada Tiang/Dinding (Kit termasuk)
WIRELESS FEATURES	
Concurrent Clients	100+
Wireless Standards	IEEE 802.11n/g/b
Frequency	2,4 GHz
Signal Rate	• 11n: Up to 300 Mbps (dynamic) • 11g: Up to 54 Mbps (dynamic) • 11b: Up to 11 Mbps (dynamic)

www.citraweb.com

Wireless Functions	• Multiple SSIDs (Up to 8 SSIDs) • Enable/Disable Wireless Radio • Automatic Channel Assignment • Transmit Power Control (Adjust Transmit Power on dBm) • QoS(WMM) • Load Balance • Rate Limit • Reboot Schedule • Wireless Schedule • Wireless Statistics based on SSID/AP/Client
Wireless Security	• Captive Portal Authentication • Access Control • Wireless Mac Address Filtering • Wireless Isolation Between Clients • SSID to VLAN Mapping • Rogue AP Detection • 802.1X Support • 64/128/152-bit WEP / WPA / WPA2-Enterprise, WPA-PSK / WPA2-PSK
Transmission Power	• CE: ≤20 dBm (EIRP) • FCC: ≤22 dBm
Certification	CE, FCC
Package Content	• 300Mbps Wireless N Outdoor Access Point, EAP110-Outdoor • Passive PoE Adapter • Power Cord • Mounting Kits • Waterproof Rubber Insert • Waterproof Antennas • Installation Guide
Environment	• Operating Temperature: -30 - 65 °C (-22 - 149 °F) • Storage Temperature: -40 - 70 °C (-40 - 158 °F) • Operating Humidity: 10%–90% non-condensing • Storage Humidity: 5%–90% non-condensing

www.citraweb.com

Download Datasheet

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1591/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com