CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

TP-LINK EAP115-Wall OMADA 300Mbps Wireless N Wall-Plate Access Point



Kode : EAP115-Wall
Brand : TP-Link Omada
Jenis : Wireless Indoor
Harga : Rp 342.000,00

TP-LINK EAP115-Wall OMADA merupakan perangkat wall access point **Single-Band** 2.4GHz dengan kecepatan up to 300Mbps. Access point ini memiliki 1 port uplink Fast Ethernet (Support 802.3af PoE) dan 1 port downlink Fast Ethernet.

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

***Produk ini belum termasuk PoE Adapter.**
***Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**

Penawaran Harga Spesial
08112039555

- **Terintegrasi ke dalam Omada SDN** : Zero-Touch Provisioning (ZTP), Manajemen Cloud Terpusat, dan Pemantauan Cerdas.
- **Manajemen Terpusat** : Akses cloud dan aplikasi Omada untuk kenyamanan maksimal dan manajemen yang mudah.
- **Tampilan Elegan** : Desain sangat tipis dengan ketebalan hanya 11 mm, sama dengan ukuran dan bentuk sakelar lampu atau pelat muka stopkontak agar pas sempurna di ruangan mana pun.
- **Pemasangan Mudah dan Dukungan PoE** : Konstruksi mudah dipasang, kompatibel dengan kotak sambungan standar 86 mm & EU, dan dukungan PoE 802.3af.
- **Jaringan Tamu Aman** : Dilengkapi dengan berbagai pilihan otentikasi (SMS/Facebook Wi-Fi/Voucher, dll.) dan teknologi keamanan nirkabel yang melimpah.

www.citraweb.com

CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com



Spesifikasi

Model	EAP115-Wall
HARDWARE FEATURES	
Interface	• Uplink: 1x Port Ethernet 10/100 Mbps • Downlink: 1x Port Ethernet 10/100 Mbps
Button	• LED/Wi-Fi Button • RESET
Power Supply	PoE (IEEE 802.3af)
Max. Power Consumption	2.8 W
Dimensions (W x D x H)	3.4 × 3.4 × 1.2 in (86.8 × 86.8 × 30.2 mm)
Antenna	Internal 2× 1.8 dBi Omni
Mounting	Wall Plate Mounting
Hardware Watch Dog	Yes
WIRELESS FEATURES	
Coverage	300 ft² (25m²)
Concurrent Clients	100+
Wireless Standards	IEEE 802.11n/g/b
Frequency	2.4 GHz
Signal Rate	• 11n: Up to 300 Mbps (dynamic) • 11g: Up to 54 Mbps (dynamic) • 11b: Up to 11 Mbps (dynamic)

www.citraweb.com

Wireless Functions	• Multiple SSIDs (Up to 8 SSIDs) • Enable/Disable Wireless Radio • Automatic Channel Assignment • Transmit Power Control (Adjust Transmit Power on dBm) • QoS(WMM) • Load Balance • Rate Limit • Reboot Schedule • Wireless Schedule • Wireless Statistics based on SSID/AP/Client
Wireless Security	• Captive Portal Authentication • Access Control • Wireless Mac Address Filtering • Wireless Isolation Between Clients • SSID to VLAN Mapping • Local LAN port based VLAN • Rogue AP Detection • 802.1X Support • 64/128/152-bit WEP / WPA / WPA2-Enterprise, WPA-PSK / WPA2-PSK
Transmission Power	CE : ≤20 dBm (2.4 GHz)
Certification	CE
Package Content	• 300 Mbps Wireless N Wall-Plate Access Point EAP115-Wall • Installation Guide • Mounting Screw
Environment	• Operating Temperature: 0 - 40 °C (32 - 104 °F) • Storage Temperature: -40 - 70 °C (-40 - 158 °F) • Operating Humidity: 10%–90% non-condensing • Storage Humidity: 5%–90% non-condensing

www.citraweb.com

Download Datasheet

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1592/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com