

TP-LINK ES220GMP OMADA 20-Port Gigabit Easy Managed Switch with 16-Port PoE+

Kode : ES220GMP

Brand : TP-Link Omada

Jenis : Switch Managed POE

Harga : Rp 3.338.000,00




TP-LINK ES220GMP OMADA merupakan switch layer 2 dengan casing 1U rackmount, 16 port Gigabit 802.3af/at PoE+ dengan max PoE budget 250 W (up to 30 W per port), 2 port Gigabit RJ45 dan 2 port SFP 1G.

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial

 **08112039555**

- 18 port RJ45 10/100/1000Mbps (16 PoE+ yang sesuai dengan standar 802.3af/at)
- 2 slot SFP Gigabit
- Anggaran daya 250W, dengan up to 30W untuk setiap port PoE
- Mudah Digunakan: Mendukung plug-and-play untuk konektivitas instan dan konfigurasi sederhana untuk fitur tambahan.
- Manajemen Cloud Terpusat melalui web atau Aplikasi Omada
- Pencegahan Loop Otomatis, VLAN, dan IGMP Snooping
- Casing logam yang tahan lama dan desain yang dapat dipasang di rak



Spesifikasi

Model	ES220GMP
HARDWARE FEATURES	
Interface	• 16× 10/100/1000 Mbps PoE+ RJ45 Ports (802.3af/at-compliant PoE+) • 2× 10/100/1000 Mbps RJ45 Ports • 2× Gigabit SFP Slots • Auto-Negotiation/Auto MDI/MDIX
Fan	1

Physical Security Lock	Yes
Power Supply	100-240 V AC~50/60 Hz
PoE Ports (RJ45)	• Standard: 802.3af PoE and 802.3at PoE+ compliant • PoE Ports: 16 ports • PoE Budget: 250W available for all PoE+ ports, 30W max per port • Fast PoE & Perpetual PoE • PoE Auto Recovery
Dimensions (W x D x H)	17.3 x 7.1 x 1.7 in.(440 x 180 x 44 mm)
Surge Protection	±6 kV
Mounting	Rack Mountable
Max. Power Consumption	289.7 W (110V/60Hz) (with 250 W PD connected)
Max. Heat Dissipation	984.88 BTU/hr (110 V/60 Hz) (with 250 W PD connected)
Packet Buffer Memory	4 Mbit
Switching Capacity	40 Gbps
Packet Forwarding Rate	29.76 Mpps
MAC Address Table	8K
Jumbo Frame	15 KB
Transmission Method	Store and Forward
SOFTWARE FEATURES	
Quality of Service	• Port-based/802.1p/DSCP QoS • 8 Priority Queues • Priority Schedule Mode - WRR (Weighted Round Robin) • Queue Weight Config • Bandwidth Control - Port-Based Rating Limit • Storm Control - Multiple Control Modes (kbps/pps) - Broadcast/Multicast/Unknown-Unicast Control

L2 Features	• Link Aggregation - Static Link Aggregation - Up to 4 aggregation groups and up to 6 ports per group • Port Isolation • Loopback Detection • Flow Control - 802.3x Flow Control • Mirroring - Port Mirroring - One-to-One - Many-to-One - Ingress/Egress/Both • Port Statistics - Port Mirror Status - Traffic Statistics • 802.1ab LLDP • IEEE 802.3az EEE
L2 Multicast	• IGMP Snooping - IGMP v1/v2/v3 Snooping - Fast Leave
VLAN	• 802.1Q Tag VLAN - Max 32 VLAN Groups - 4K VID
OTHERS	
Certification	CE, FCC
Package Content	• ES220GMP • Power Cord • Mounting Brackets • Mounting Feet • Screws • Installation Guide
Environment	• Operating Temperature: -5-50C (23-122F) • Storage Temperature: -40-70C (-40-158F) • Operating Humidity: 10-90% RH non-condensing • Storage Humidity: 5-90% RH non-condensing

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1603/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com