

TP-LINK ER605 OMADA Gigabit VPN Gateway

Kode : ER605**Brand** : TP-Link Omada**Jenis** : Router Desktop**Harga** : Rp 1.053.000,00

TP-LINK ER605 OMADA merupakan perangkat gateway dilengkapi dengan 5 port gigabit (1 port fixed WAN, 2 port fixed LAN dan 2 port WAN/LAN). Perangkat ini juga memiliki 1 port USB 2.0 yang mendukung Dongle USB LTE, Support load balancing hingga 3 WAN.

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial **08112039555**

- **Terintegrasi ke dalam Omada SDN** : Penyediaan Tanpa Sentuhan (Zero-Touch Provisioning), Manajemen Cloud Terpusat, dan Pemantauan Cerdas.
- **Manajemen Cloud Terpusat** : Akses cloud dan aplikasi Omada untuk kenyamanan dan pengelolaan yang mudah.
- **Lima Port Gigabit** : Konektivitas kabel berkecepatan tinggi.
- **Hingga 3 Port Ethernet WAN** : 1 port WAN Gigabit dan 2 port WAN/LAN Gigabit dengan penyeimbangan beban meningkatkan tingkat pemanfaatan broadband multi-jalur.
- **Satu Port WAN USB untuk Broadband Seluler** : Broadband seluler melalui modem 4G/3G didukung untuk cadangan WAN dengan menghubungkan ke port USB.
- **VPN yang Sangat Aman** : Mendukung hingga 20 koneksi LAN-ke-LAN IPsec, 50 koneksi OpenVPN, 16 koneksi L2TP, dan 16 koneksi PPTP VPN.
- **Fitur Keamanan yang Melimpah** : Kebijakan firewall tingkat lanjut, pertahanan DoS, pemfilteran IP/MAC/URL, dan lebih banyak fungsi keamanan melindungi jaringan dan data Anda.





Spesifikasi

Model	ER605
HARDWARE FEATURES	
Interface	• 1 Gigabit WAN port • 2 Gigabit WAN/LAN ports • 2 Gigabit LAN ports • 1 USB2.0 (supports USB LTE dongle)
Button	Reset Button
Power Supply	External 12V/1A DC Adapter
Flash	128 MB NAND
DRAM	256 MB
LED	PWR, SYS, WAN (Link/Act), LAN (Link/Act), USB
Dimensions (W x D x H)	6.2 x 4.0 x 1.0 in (158 x 101 x 25mm)
Mounting	Desktop/Wall-mount
Max. Power Consumption	7.94 W

PERFORMANCE	
Concurrent Session	150,000
New Sessions /Second	1,800
OpenVPN	15.90 Mbps
WireGuard VPN Throughput	82.62 Mbps
SOFTWARE FEATURES	
LAN DNS	Yes
WAN Connection Type	• Static • Dynamic IP • PPPoE (supports MRU Configuration) • PPTP • L2TP
MAC Clone	Modify WAN/LAN MAC Address
DHCP	• DHCP Server • DHCPv6 PD Server (only in Standalone Mode) • DHCP Options Customization • DHCP Address Reservation • Multi-IP Interfaces • Multi-Net DHCP • WAN DHCP 60
Basic Function	• Stateful ACL • Quality of Service • Bridge VLAN • mDNS Repeater
IPv6	StaticIP/SLAAC/DHCPv6/PPPoE/6to4Tunnel/PassThrough/Non-Address mode
VLAN	802.1Q VLAN
IPTV	IGMP v2/v3 Proxy, Custom Mode, Bridge Mode
Advanced Routing	• Static Routing • Policy Routing • RIP • OSPF
Bandwidth Control	IP-based Bandwidth Control
Load Balance	• Intelligent Load Balance • Application Optimized Routing • Link Backup (Timing, Failover) • Online Detection

NAT	• One-to-One NAT • Multi-Net NAT • Port Forwarding • Port Triggering • NAT-DMZ • FTP/H.323/SIP/IPSec/PPTP ALG • UPnP • Disable NAT
Session Limit	IP-based Session Limit
OTHERS	
Certification	CE, FCC
Package Content	• ER605 • Power Adapter • RJ-45 Ethernet Cable • Quick Installation Guide
Environment	• Operating Temperature: 0-40C (32-104F) • Storage Temperature: -40-70C (-40-158F) • Operating Humidity: 10-90% RH non-condensing • Storage Humidity: 5-90% RH non-condensing

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1621/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com