CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

TP-LINK TL-SG105MPE OMADA 5-Port Gigabit Easy Smart Switch with 4-Port PoE+



Kode : TL-SG105MPE
Brand : TP-Link Omada
Jenis : Switch Managed POE
Harga : Rp 1.026.000,00

TP-LINK TL-SG105MPE OMADA merupakan switch layer 2 dengan casing Desktop dilengkapi 5 port 10/10/1000 Mbps (4 port support PoE+ up to 120 W).

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial
08112039555

- **5 port RJ45 10/100/1000Mbps**
- **Dilengkapi dengan 4 port PoE+ 802.3af/at dengan daya hingga 30W untuk setiap port, data dan daya dapat ditransfer melalui satu kabel tunggal.**
- **Mendukung daya PoE hingga 120 W**
- **Menyediakan pemantauan jaringan, prioritas lalu lintas, fitur VLAN, dan pemulihan otomatis PoE**
- **Pengaturan jaringan yang sederhana di atas konektivitas plug-and-play**
- **Antarmuka pengguna berbasis web dan Easy Smart Configuration Utility menyederhanakan konfigurasi**
- **Desain tanpa kipas mengurangi konsumsi energi dan menghilangkan kebisingan saat beroperasi**

Spesifikasi

Model	TL-SG105MPE
HARDWARE FEATURES	
Interface	5× 10/100/1000 Mbps RJ45 Ports AUTO Negotiation/AUTO MDI/MDIX
Fan	Fanless
Physical Security Lock	Yes
Power Supply	External Power Adapter (Output: 53.5 VDC / 2.43 A)

www.citraweb.com

CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

PoE Ports (RJ45)	Standard: 802.3 af/at compliant PoE Ports: Port 1- Port 4 PoE Power Budget: 120 W
Dimensions (W x D x H)	3.9 × 3.9 × 1.0 in (99.8 × 98 × 25 mm)
Max. Power Consumption	4.34 W (220 V/50 Hz with no PD connected) 137.01 W (110 V/50 Hz with 120 W PD connected)
Max. Heat Dissipation	14.8 BTU/h (with no PD connected) 467.17 BTU/h (with 120 W PD connected)
Packet Buffer Memory	1 Mb
Switching Capacity	10 Gbps
Packet Forwarding Rate	7.44 Mpps
MAC Address Table	2K
Jumbo Frame	16 KB
SOFTWARE FEATURES	
Quality of Service	Support Port-based 802.1p/DSCP priority Support 4 priority queues Rate Limit Storm Control
L2 Features	IGMP Snooping V1/V2/V3 Static Link Aggregation Port Mirroring Cable Diagnostics Loop Prevention PoE Auto Recovery Extend Mode
VLAN	Supports up to 32 VLANs simultaneously (out of 4K VLAN IDs) MTU/Port/Tag VLAN
Transmission Method	Store-And-Forward
OTHERS	
Certification	CE, FCC
Package Content	TL-SG105MPE Power Adapter Installation Guide Rubber Feet

www.citraweb.com

Environment	• Operating Temperature: 0~40C (32~104F) • Storage Temperature: -40–70C (-40–158F) • Operating Humidity: 10–90% RH non-condensing • Storage Humidity: 5–90% RH non-condensing

Download Datasheet

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1673/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com