CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

TP-LINK TL-SG1218MP OMADA 18-Port Gigabit Rackmount Unmanaged Switch with 16 PoE+



Kode : TL-SG1218MP
Brand : TP-Link Omada
Jenis : Switch Unmanaged POE
Harga : Rp 2.823.000,00

TP-LINK TL-SG1218MP OMADA merupakan unmanaged switch yang dilengkapi 16 port Gigabit PoE+, 2 port Gigabit non-PoE dan 2 port Combo Gigabit SFP. Menggunakan standard IEEE 802.3af/at yang mampu memberikan daya PoE hingga 250W (maksimal 30W pada setiap port).

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial
08112039555

- **16 port RJ45 PoE+ gigabit, 2 port RJ45 non-PoE gigabit, dan 2 slot SFP gigabit kombo**
- **Anggaran daya PoE tinggi hingga 30 W untuk setiap port PoE dan 250 W untuk semua port PoE**
- **Bekerja dengan PD yang sesuai dengan standar IEEE 802.3af/at**
- **Plug-and-Play, tanpa perlu konfigurasi dan instalasi**
- **QoS 802.1p/DSCP memungkinkan kelancaran lalu lintas yang sensitif terhadap latensi.**
- **Casing logam yang tahan lama dan desain pembuangan panas profesional memastikan rentang suhu operasi yang luas (0-50C).**

www.citraweb.com

CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

BACK VIEW



Spesifikasi

Model	TL-SG1218MP
HARDWARE FEATURES	
Interface	• 16 port RJ45 gigabit PoE+ • 2 port RJ45 gigabit non-PoE • 2 slot SFP gigabit combo
Fan	2
Physical Security Lock	Yes
Power Supply	100–240 VAC, 50/60 Hz
PoE Ports (RJ45)	• Standard: 802.3at/802.3af compliant • PoE Ports: Ports 1–16 • PoE Power Budget: 250 W
Dimensions (W x D x H)	17.3 × 7.1 × 1.73 in (440 × 180 × 44 mm)
Mounting	Rack Mountable
Max. Power Consumption	• 21.4 W (220/50 Hz. no PD connected) • 286.64 W (220/50 Hz. with 250 W PD connected)
Max. Heat Dissipation	• 72.97 BTU/h (no PD connected) • 977.44 BTU/h (with 250 W PD connected)
Packet Buffer Memory	4.1 Mbit
Jumbo Frame	10 KB

www.citraweb.com

Switching Capacity	36 Gbps
Packet Forwarding Rate	26.78 Mbps
MAC Address Table	8K
Advanced Features	• Compatible With IEEE 802.3af/at Compliant PDs • 802.1p/DHCP QoS • Mac Address Auto-Learning And Auto-Aging • IEEE802.3x Flow Control For Full-Duplex Mode And Backpressure For Half-Duplex Mode
OTHERS	
Certification	CE, FCC
Package Content	• TL-SG1218MP • Installation Guide • Power Cord • Rackmount Kit • Rubber Feet
Environment	• Operating Temperature: 0–50 C (32–122 F) • Storage Temperature: -40–70 C (-40–158 F) • Operating Humidity: 10–90% RH non-condensing • Storage Humidity: 5–90% RH non-condensing

Download Datasheet

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1686/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com