CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

TP-LINK TL-SG1210MP OMADA 10-Port Gigabit Desktop Unmanaged Switch with 8-Port PoE+



Kode : TL-SG1210MP
Brand : TP-Link Omada
Jenis : Switch Unmanaged POE
Harga : Rp 1.710.000,00

TP-LINK TL-SG1210MP OMADA merupakan unmanaged switch yang dilengkapi 8 port Gigabit PoE+, 1 port Gigabit non-PoE dan 1 port Combo Gigabit SFP/RJ45. Menggunakan standard IEEE 802.3af/at yang mampu memberikan daya PoE hingga 123W (maksimal 30W pada setiap port).

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial
08112039555

- **9 port gigabit RJ45, dan 1 port gigabit combo SFP/RJ45.**
- **8 port PoE+ mentransfer data dan daya melalui satu kabel dengan total daya yang dibutuhkan sebesar 123 W.**
- **Sesuai dengan standar IEEE 802.3af/at PoE+, switch ini mendukung daya PoE hingga 30 W untuk setiap port PoE.**
- **Mode Prioritas memastikan prioritas tinggi pada port 1–2 untuk menjamin kualitas aplikasi sensitif.**
- **Mode Isolasi memungkinkan pemisahan lalu lintas klien dengan sekali klik untuk keamanan dan kinerja yang lebih tinggi.**
- **Secara otomatis melakukan reboot perangkat bertenaga PoE Anda yang terputus atau tidak responsif dengan PoE Auto Recovery.**
- **Pasang dan mainkan tanpa perlu konfigurasi.**
- **Desain tanpa kipas mengurangi konsumsi daya dan bekerja tanpa suara di lokasinya.**

www.citraweb.com

CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

BACK VIEW



Spesifikasi

Model	TL-SG1210MP
HARDWARE FEATURES	
Interface	• 9× 10/100/1000 Mbps RJ45 Ports • 1× 1000 Mbps Combo SFP/RJ45 Port • AUTO Negotiation • AUTO MDI/MDIX
Fan	Fanless
Physical Security Lock	Yes
Power Supply	External Power Adapter (Output: 53.5VDC / 2.43A)
PoE Ports (RJ45)	• Standard: 802.3 af/at compliant • PoE Ports: Ports 1–8 • Power Supply: 123 W
Dimensions (W x D x H)	8.2 × 4.9 × 1.0 in (209 × 126 × 26 mm)
Mounting	Desktop
Max. Power Consumption	• 7.93 W (220V / 50Hz with no PD connected) • 141.40 W (220V / 50Hz with 123 W PD connected)
Max. Heat Dissipation	• 27.04 BTU/h (220V / 50Hz with no PD connected) • 482.17 BTU/h (220V / 50Hz with 123 W PD connected)
Jumbo Frame	16 KB
Switching Capacity	20 Gbps

www.citraweb.com

Packet Forwarding Rate	14.88 Mpps
MAC Address Table	4K
Advanced Features	• Compatible With IEEE 802.3af/at Compliant PDs • Extend Mode Button (Ports 1–4, Up to 250 m PoE power supply and data transmission) • Priority Mode Button (Ports 1–2) • Isolation Mode Button (Ports 1–4 / 5-8) • PoE Auto Recovery (Ports 1-8) • Mac Address Auto-Learning and Auto-Aging • IEEE802.3x Flow Control For Full-Duplex Mode And Backpressure for Half-Duplex Mode
OTHERS	
Certification	CE, FCC
Package Content	• TL-SG1210MP • Power Adapter • Installation Guide
Environment	• Operating Temperature: 0–40 C (32–104 F) • Storage Temperature: -40–70 C (-40–158 F) • Operating Humidity: 10–90% RH non-condensing • Storage Humidity: 5–90% RH non-condensing

Download Datasheet

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1687/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com