CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

TP-LINK TL-SG1210P OMADA 10-Port Gigabit Desktop Unmanaged Switch with 8-Port PoE+



Kode : TL-SG1210P
Brand : TP-Link Omada
Jenis : Switch Unmanaged POE
Harga : Rp 1.197.000,00

TP-LINK TL-SG1210P OMADA merupakan unmanaged switch yang dilengkapi 8 port Gigabit PoE+, 1 port Gigabit non-PoE dan 1 port Gigabit SFP. Menggunakan standard IEEE 802.3af/at yang mampu memberikan daya PoE hingga 63W.

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial
08112039555

- **9 port RJ45 10/100/1000Mbps, 1 port SFP Gigabit.**
- **Dengan 8 port PoE+, mentransfer data dan daya hanya melalui satu kabel.**
- **Kompatibel dengan PD yang sesuai dengan standar IEEE 802.3af/at dan memperluas jaringan kantor.**
- **QoS 802.1p/DSCP memungkinkan kelancaran lalu lintas yang sensitif terhadap latensi.**
- **Anggaran daya PoE tinggi hingga 30W untuk setiap port PoE dan 63W untuk semua port PoE.**
- **Mudah digunakan, tanpa perlu konfigurasi dan instalasi.**

www.citraweb.com

BACK VIEW



CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

Spesifikasi

Model	TL-SG1210P
HARDWARE FEATURES	
Interface	8 Port RJ45 PoE+ 10/100/1000Mbps 1 Port RJ45 10/100/1000Mbps 1 Slot SFP Gigabit
Fan	Fanless
Physical Security Lock	Yes
Power Supply	External Power Adapter (Output: 53.5VDC / 1.31A)
PoE Ports (RJ45)	Standard: 802.3at/802.3af compliant PoE Ports: Port1- Port 8 PoE Power Budget: 63W
Dimensions (W x D x H)	8.2 × 4.9 × 1.0 in (209 × 126 × 26 mm)
Mounting	Desktop
Max. Power Consumption	7.11 W (220/50Hz. no PD connected) 78.13 W (220/50Hz. with 63W PD connected)
Max. Heat Dissipation	24.25 BTU/h (no PD connected) 266.42 BTU/h (with 63W PD connected)
Jumbo Frame	16 KB
Switching Capacity	20 Gbps
Packet Forwarding Rate	14.88 Mpps
MAC Address Table	4K
Advanced Features	Compatible With IEEE 802.3af/at Compliant PDs EEE802.3x Flow Control 802.1p/DSCP QoS IGMP Snooping
OTHERS	
Certification	CE, FCC
Package Content	• TL-SG1210P • Power Adapter • Installation Guide

www.citraweb.com

Environment	• Operating Temperature: 0–40 C (32–104 F) • Storage Temperature: -40–70 C (-40–158 F) • Operating Humidity: 10–90% RH non-condensing • Storage Humidity: 5–90% RH non-condensing

Download Datasheet

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1688/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com