CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

TP-LINK TL-SG1005P OMADA 5-Port Gigabit Desktop Unmanaged Switch with 4-Port PoE+



Kode : TL-SG1005P
Brand : TP-Link Omada
Jenis : Switch Unmanaged POE
Harga : Rp 488.000,00

TP-LINK TL-SG1005P OMADA merupakan unmanaged switch yang dilengkapi 5 port Gigabit dengan 4 port support PoE+ standard IEEE 802.3af/at yang mampu memberikan daya PoE hingga 65W.

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial
08112039555

- **5 port RJ45 10/100/1000 Mbps**
- **Dengan empat port PoE+, mentransfer data dan daya melalui satu kabel tunggal.**
- **Kompatibel dengan PD yang sesuai dengan standar IEEE 802.3af/at.**
- **QoS 802.1p/DSCP memungkinkan kelancaran lalu lintas yang sensitif terhadap latensi.**
- **Mendukung daya PoE hingga 30 W untuk setiap port PoE.**
- **Mendukung daya PoE hingga 65 W untuk semua port PoE.**
- **PoE Auto Recovery menjamin pengoperasian perangkat PoE yang stabil dengan secara otomatis melakukan reboot perangkat PD yang terputus atau tidak responsif.**
- **Plug-and-Play, tidak perlu konfigurasi dan instalasi.**

Spesifikasi

Model	TL-SG1005P
HARDWARE FEATURES	
Interface	• 5× 10/100/1000Mbps RJ45 Ports • AUTO Negotiation • AUTO MDI/MDIX
Fan	Fanless
Power Supply	External Power Adapter (Output: 53.5 VDC / 1.31 A)

www.citraweb.com

PoE Ports (RJ45)	• Standard: 802.3 af/at compliant • PoE Ports: Ports 1–4 • Power Supply: 65 W
Dimensions (W x D x H)	3.9×3.9×1.0 in (99.8×98×25 mm)
Max. Power Consumption	• 3.44 W (220/50 Hz. no PD connected) • 74.49 W (220/50 Hz. with 65 W PD connected)
Max. Heat Dissipation	• 11.73 BTU/h (no PD connected) • 254.01 BTU/h (with 65 W PD connected)
Jumbo Frame	16 KB
Switching Capacity	10 Gbps
Packet Forwarding Rate	7.44 Mpps
MAC Address Table	2K
Advanced Features	• Compatible With IEEE 802.3af/at Compliant PDs • Mac Address Auto-Learning And Auto-Aging • IEEE 802.3x Flow Control • 802.1p/DSCP QoS • IGMP Snooping • Extend Mode Button (Ports 1–2, Up to 250 m PoE power supply and data transmission) • PoE Auto Recovery (Ports 1-4)
OTHERS	
Certification	CE, FCC
Package Content	TL-SG1005P Power Adapter Installation Guide
Environment	• Operating Temperature: 0–40 C (32–104 F) • Storage Temperature: -40–70 C (-40–158 F) • Operating Humidity: 10–90% RH non-condensing • Storage Humidity: 5–90% RH non-condensing

www.citraweb.com

Download Datasheet

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1693/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com