CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

TP-LINK TL-SL1218MP OMADA 16-Port PoE+ 10/100Mbps 2-Port Gigabit Unmanaged Switch



Kode : TL-SL1218MP
Brand : TP-Link Omada
Jenis : Switch Unmanaged POE
Harga : Rp 2.225.000,00

TP-LINK TL-SL1218MP OMADA merupakan unmanaged switch yang dilengkapi 16 port PoE+ 10/100 Mbps RJ45, 2 port Gigabit RJ45 dan 2 port Combo Gigabit SFP. Switch ini mampu memberikan daya PoE hingga 250W.

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial
08112039555

- **16 port PoE+ 10/100Mbps RJ45, 2 port Gigabit RJ45, dan 2 slot combo Gigabit SFP.**
- **Transmisi data dan daya hingga 250m dalam mode jangkauan luas, dirancang khusus untuk sistem pengawasan.**
- **Mode prioritas untuk port 1-8 untuk menjamin kualitas aplikasi sensitif seperti monitor video.**
- **Anggaran daya PoE tinggi hingga 30W untuk setiap port PoE dan 250W untuk semua port PoE.**
- **Mudah digunakan, tanpa perlu konfigurasi dan instalasi.**

BACK VIEW



www.citraweb.com

Spesifikasi

Model	TL-SL1218MP

CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

HARDWARE FEATURES	
Interface	• 16 PoE+ 10/100 Mbps RJ45 Ports • 2× 10/100/1000 Mbps RJ45 Ports • 2× Combo Gigabit SFP Slots
Fan	2 Fans
Physical Security Lock	Yes
Power Supply	100–240V AC, 50/60 Hz
PoE Ports (RJ45)	• Standard: 802.3at/802.3af compliant • PoE Ports: Ports 1–16 • PoE Power Budget: 250 W
Dimensions (W x D x H)	17.3 × 7.1 × 1.7 in (440 × 180 × 44 mm)
Max. Power Consumption	• 12.55 W (220/50Hz. no PD connected) • 301.71 W (220/50Hz. with 250 W PD connected)
Max. Heat Dissipation	• 42.67 BTU/h (no PD connected) • 1025.81 BTU/h (with 250 W PD connected)
Jumbo Frame	10 KB
Switching Capacity	7.2 Gbps
Packet Forwarding Rate	5.36 Mpps
MAC Address Table	8K
Advanced Features	• Compatible With IEEE 802.3at/af Compliant PDs • Extend Mode (Up to 250m PoE power supply and data transmission) • Priority Mode (Ports 1-8) • Isolation Mode (Ports 1-16) • PoE Auto Recovery (Ports 1-16) • Mac Address Auto-Learning And Auto-Aging • IEEE802.3x Flow Control
OTHERS	
Certification	CE, FCC
Package Content	• TL-SL1218MP • Power Cable • Installation Guide • Two mounting brackets and the fittings
Environment	• Operating Temperature: 0–50 C (32–122 F) • Storage Temperature: -40–70 C (-40–158 F) • Operating Humidity: 10–90% RH non-condensing • Storage Humidity: 5–90% RH non-condensing

www.citraweb.com

Download Datasheet

* *Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1698/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com