CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

TP-LINK TL-SF1008P OMADA 8-Port 10/100Mbps Desktop Unmanaged Switch with 4-Port PoE+



Kode : TL-SF1008P
Brand : TP-Link Omada
Jenis : Switch Unmanaged POE
Harga : Rp 547.000,00

TP-LINK TL-SF1008P OMADA merupakan unmanaged switch yang dilengkapi 8 Port 10/100 Mbps RJ45 (4 Port support 802.3af/at PoE+). Switch ini mampu memberikan daya PoE hingga 66W.

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial
08112039555

- **8 port RJ45 10/100 Mbps**
- **4 port PoE+ mentransfer data dan daya melalui kabel terpisah.**
- **Kompatibel dengan PD yang sesuai dengan standar IEEE 802.3af/at.**
- **Mendukung daya PoE hingga 30 W untuk setiap port PoE.**
- **Mendukung daya PoE hingga 66 W untuk semua port PoE.**
- **Mode Prioritas memastikan prioritas tinggi pada port 1–2 untuk menjamin kualitas aplikasi sensitif.**
- **PoE Auto Recovery menjamin pengoperasian perangkat PoE yang stabil dengan secara otomatis melakukan reboot perangkat PD yang terputus atau tidak responsif.**
- **Desain tanpa kipas mengurangi konsumsi daya dan bekerja tanpa suara di lokasinya.**
- **Plug-and-Play, tanpa perlu konfigurasi dan instalasi.**

www.citraweb.com

CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

BACK VIEW



Spesifikasi

Model	TL-SF1008P
HARDWARE FEATURES	
Interface	• 8× 10/100 Mbps RJ45 Ports (4× 10/100 Mbps 802.3af/at PoE+ ports) • AUTO Negotiation • AUTO MDI/MDIX
Fan	Fanless
Physical Security Lock	Yes
Power Supply	External Power Adapter (Output: 53.5VDC / 1.31A)
PoE Ports (RJ45)	• Standard: 802.3 af/at compliant • PoE Ports: Ports 1–4 • Power Supply: 66 W
Dimensions (W x D x H)	6.7 × 3.9 × 1.1 in (171 × 98 × 27 mm)
Max. Power Consumption	2.27 W (220 V/ 50 Hz. no PD connected) 75.33 W (220 V/ 50 Hz. with 66 W PD connected)
Max. Heat Dissipation	7.74 BTU/h(no PD connected) 256.88 BTU/h(with 66 W PD connected)
Jumbo Frame	2 KB
Switching Capacity	1.6 Gbps
Packet Forwarding Rate	1.1904 Mpps

www.citraweb.com

MAC Address Table	2K
Advanced Features	Extend Mode Button (Ports 1–4) Priority Mode Button (Ports 1–2) PoE Auto Recovery Button (Ports 1–4) Mac Address Auto-Learning and Auto-Aging
OTHERS	
Certification	CE, FCC
Package Content	TL-SF1008P, Power Adapter, Installation Guide, Rubber Feet
Environment	• Operating Temperature: 0–40 C (32–104 F) • Storage Temperature: -40–70 C (-40–158 F) • Operating Humidity: 10–90% RH non-condensing • Storage Humidity: 5–90% RH non-condensing

Download Datasheet

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1702/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com