CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

TP-LINK TL-SF1005P OMADA 6-Port 10/100Mbps Desktop Unmanaged Switch with 4-Port PoE+



Kode : TL-SF1005P
Brand : TP-Link Omada
Jenis : Switch Unmanaged POE
Harga : Rp 452.000,00

TP-LINK TL-SF1005P OMADA merupakan unmanaged switch yang dilengkapi 5 Port 10/100 Mbps RJ45 (4 Port support 802.3af/at PoE+). Switch ini mampu memberikan daya PoE hingga 67W.

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial
08112039555

- **5 port RJ45 10/100 Mbps.**
- **4 port PoE+ mentransfer data dan daya melalui kabel terpisah.**
- **Kompatibel dengan PD yang sesuai dengan standar IEEE 802.3af/at.**
- **Mendukung daya PoE hingga 30 W untuk setiap port PoE.**
- **Mendukung daya PoE hingga 67 W untuk semua port PoE.**
- **Mode Prioritas memastikan prioritas tinggi pada port 1–2 untuk menjamin kualitas aplikasi yang sensitif.**
- **PoE Auto Recovery menjamin pengoperasian perangkat PoE yang stabil dengan secara otomatis melakukan reboot perangkat PD yang terputus atau tidak responsif.**
- **Plug-and-Play, tanpa perlu konfigurasi dan instalasi.**

www.citraweb.com



Spesifikasi

Model	TL-SF1005P
HARDWARE FEATURES	
Interface	• 5× 10/100 Mbps RJ45 Ports (4× 10/100 Mbps 802.3af/at PoE+ ports) • AUTO Negotiation • AUTO MDI/MDIX
Fan	Fanless
Physical Security Lock	Yes
Power Supply	External Power Adapter (Output: 53.5VDC / 1.31A)
PoE Ports (RJ45)	• Standard: 802.3 af/at compliant • PoE Ports: Ports 1–4 • Power Supply: 67 W
Dimensions (W x D x H)	3.9 x 3.9 x 1.0 in (99.8 x 98 x 25 mm)
Max. Power Consumption	• 1.9 W (220 V / 50 Hz, no PD connected) • 74 W (220 V / 50 Hz, with 67 W PD connected)
Max. Heat Dissipation	• 6.48 BTU/h(no PD connected) • 252.34 BTU/h(with 67 W PD connected)
Jumbo Frame	2 KB
Switching Capacity	1 Gbps
Packet Forwarding Rate	0.744 Mpps

www.citraweb.com

MAC Address Table	2K
Advanced Features	• Compatible With IEEE 802.3af/at Compliant PDs • Extend Mode Button (Ports 1–4) • Priority Mode Button (Ports 1–2) • Mac Address Auto-Learning And Auto-Aging • IEEE802.3x Flow Control For Full-Duplex Mode And Backpressure For Half-Duplex Mode
OTHERS	
Certification	CE, FCC
Package Content	• TL-SF1005P • Power Adapter • Installation Guide
Environment	• Operating Temperature: 0–40 C (32–104 F) • Storage Temperature: -40–70 C (-40–158 F) • Operating Humidity: 10–90% RH non-condensing • Storage Humidity: 5–90% RH non-condensing

Download Datasheet

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1705/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com

www.citraweb.com