**CITRAWEB SOLUSI TEKNOLOGI**
www.citraweb.com
info@citraweb.com
sales@citraweb.com

# TP-LINK TL-SF1005LP OMADA 5-Port 10/100Mbps Desktop Unmanaged Switch with 4-Port PoE



**Kode** : TL-SF1005LP
**Brand** : TP-Link Omada
**Jenis** : Switch Unmanaged POE
**Harga** : Rp 410.000,00

**TP-LINK TL-SF1005LP OMADA** merupakan unmanaged switch yang dilengkapi 5 Port 10/100 Mbps RJ45 (4 Port support 802.3af PoE). Switch ini mampu memberikan daya PoE hingga 41W.

**Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.**

Penawaran Harga Spesial
08112039555

- **5 port RJ45 10/100 Mbps.**
- **4 port PoE mentransfer data dan daya melalui kabel terpisah.**
- **Kompatibel dengan PD yang sesuai dengan standar IEEE 802.3af.**
- **Mode Prioritas memastikan prioritas tinggi pada port 1–2 untuk menjamin kualitas aplikasi sensitif.**
- **Mendukung daya PoE hingga 41 W untuk semua port PoE.**
- **Plug-and-Play, tanpa perlu konfigurasi dan instalasi.**

**Spesifikasi**

| | |
|---|---|
| **Model** | TL-SF1005LP |
| | |
| **HARDWARE FEATURES** | |
| **Interface** | • 5× 10/100 Mbps RJ45 Ports (Ports 1–4 support 802.3af PoE)<br>• AUTO Negotiation<br>• AUTO MDI/MDIX |
| **Fan** | Fanless |
| **Physical Security Lock** | Yes |
| **Power Supply** | External Power Adapter (Output: 53.5 V DC / 0.81 A) |

www.citraweb.com

| | |
|---|---|
| **PoE Ports (RJ45)** | • Standard: 802.3 af compliant<br>• PoE Ports: Ports 1–4<br>• Power Supply: 41 W |
| **Dimensions ( W x D x H )** | 3.9×3.9×1.0 in (100×98×25 mm) |
| **Max. Power Consumption** | • 1.9 W (220 V / 50 Hz, no PD connected)<br>• 47 W (220 V / 50 Hz, with 41 W PD connected) |
| **Max. Heat Dissipation** | • 6.48 BTU/h(no PD connected)<br>• 160.27 BTU/h(with 41 W PD connected) |
| **Jumbo Frame** | 2 KB |
| **Switching Capacity** | 1 Gbps |
| **Packet Forwarding Rate** | 0.744 Mpps |
| **MAC Address Table** | 2K |
| **Advanced Features** | • Compatible With IEEE 802.3af/at Compliant PDs<br>• Extend Mode Button (Ports 1–4)<br>• Priority Mode Button (Ports 1–2)<br>• Mac Address Auto-Learning And Auto-Aging<br>• IEEE802.3x Flow Control For Full-Duplex Mode and Backpressure for Half-Duplex Mode |
| | |
| **OTHERS** | |
| **Certification** | CE, FCC |
| **Package Content** | • TL-SF1005LP<br>• Power Adapter<br>• Installation Guide |
| **Environment** | • Operating Temperature: 0–40 C (32–104 F)<br>• Storage Temperature: -40–70 C (-40–158 F)<br>• Operating Humidity: 10–90% RH non-condensing<br>• Storage Humidity: 5–90% RH non-condensing |

www.citraweb.com

**Download Datasheet**

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

**URL :** https://www.citraweb.com/produk/1706/

**Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com**