CITRAWEB SOLUSI TEKNOLOGI
www.citraweb.com
info@citraweb.com
sales@citraweb.com

TP-LINK LS106LP OMADA 9-Port 10/100Mbps Desktop Unmanaged Switch with 8-Port PoE+



Kode : LS106LP
Brand : TP-Link Omada
Jenis : Switch Unmanaged POE
Harga : Rp 335.000,00

TP-LINK LS106LP OMADA merupakan unmanaged switch LiteWave series yang dilengkapi 6 port 10/100 Mbps RJ45 auto-negotiation (Port 1-4 support PoE output maksimal 41W) menyediakan kapasitas switching hingga 1.2 Gbps.

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial
08112039555

- **Anggaran PoE 41 W** : Empat port PoE 10/100 Mbps yang sesuai dengan standar 802.3af dengan mudah menghubungkan dan memberi daya pada perangkat tetap seperti kamera IP, titik akses, dan telepon IP melalui satu kabel. Setiap port PoE mendukung output PoE hingga 15,4 W.
- **Transmisi PoE hingga 250 m** : Dengan Mode Perluasan, jarak transmisi PoE mencapai hingga 250m, sangat cocok untuk pemasangan kamera pengawasan di area yang luas.
- **PoE Auto Recovery** : Secara otomatis memulai ulang perangkat bertenaga PoE Anda yang terjatuh atau tidak responsif.
- **Plug and Play** : Cukup colokkan dan mainkan untuk konektivitas instan tanpa perlu konfigurasi.
- **Pengoperasian Senyap** : Desain tanpa kipas mengurangi konsumsi daya dan memastikan pengoperasian yang senyap, ideal untuk rumah atau bisnis yang sensitif terhadap kebisingan.
- **Desain Perangkat Keras yang Andal** : Casing logam yang tahan lama dan desain pemasangan di meja/dinding sangat cocok untuk berbagai lingkungan.

Spesifikasi

Model	LS106LP
HARDWARE FEATURES	
Interface	• 6× 10/100 Mbps RJ45 Ports (4× 10/100 Mbps 802.3af PoE Ports) • AUTO Negotiation • AUTO MDI/MDIX
Fan	Fanless
Physical Security Lock	Yes

www.citraweb.com

Power Supply	External Power Adapter (Output: 53.5VDC / 0.81A)
PoE Ports (RJ45)	• Standard: 802.3 af compliant • PoE Ports: Ports 1–4, up to 15.4 W PoE output per port • Power Supply: 41 W
Dimensions (W x D x H)	6.2×4.0×1.0 in (158×101×25 mm)
Max. Power Consumption	• 2.53 W (220 V/50 Hz no PD connected) • 47.76 W (220 V/50 Hz with 41 W PD connected)
Max. Heat Dissipation	• 8.61 BTU/h (220 V/50 Hz no PD connected) • 162.38 BTU/h (220 V/50 Hz with 41 W PD connected)
Jumbo Frame	2 KB
Switching Capacity	1.2 Gbps
Packet Forwarding Rate	0.8928 Mpps
MAC Address Table	2K
Advanced Features	• Extend Mode Button (Ports 1–4, Up to 250 m PoE power supply and data transmission) • PoE Auto Recovery Button (Ports 1-4) • Compatible With IEEE 802.3af Compliant PDs • Mac Address Auto-Learning and Auto-Aging • IEEE 802.3x Flow Control • Green Technology
OTHERS	
Certification	CE, FCC
Package Content	• LS106LP • Power Adapter • Installation Guide
Environment	• Operating Temperature: 0–40 C (32–104 F) • Storage Temperature: -40–70 C (-40–158 F) • Operating Humidity: 10–90% RH non-condensing • Storage Humidity: 5–90% RH non-condensing

www.citraweb.com

Download Datasheet

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : https://www.citraweb.com/produk/1709/

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com