

## Line Interactive UPS 800VA/480W



**Kode** : Plus3E-US800G

**Kategori** : APlus UPS System

**Harga** : Rp 570.000,00

Plus3E-US800G adalah produk dari APlus UPS System dengan rating 800VA/480Watt dan memiliki desain "Easy Battery Replacement".

Desain ini memungkinkan pengguna untuk mudah melakukan maintenance atau mengganti battery jika sudah lemah.

**\*Produk ini tidak termasuk battery**

### Features :

- Controlled by a technologically advanced microprocessor guaranteeing high reliability
- Equipped with 2-steps boost & 1-step buck AVR to stabilize output voltage
- USB port and monitor software is designed to manage UPS status via PC (Optional)
- Coaxial cable line / modem / phone protection (Optional)
- Built-in DC start function enables UPS to be started without AC power supplied
- Constant current, constant voltage battery charger (CCCV Battery Charger)
- UPS will charge itself even though power switch is off (Off mode charging)
- Over / under voltage protection (UPS will go to battery mode)
- Lightning / surge protection 175 joules
- UPS will shut down upon battery low ; UPS will restart automatically upon AC recovery (Auto-restart)
- Smart USB charging station 5VDC 2.4A max. for smart devices power charging (Optional)

### Battery Type :

- VRLA 12V/9AH
- 1 pcs
- **Battery dimension 151 x 65 x 100 mm**

### Easy Battery Replacement and Installation :

**Intelligent Battery Door Design:**


Manual :

[UPS-Aplus-Plus3E.pdf](#)

Specification :

<b>INPUT</b>	
Voltage	220/230Vac
Voltage Range	-30% +25%
Frequency	50Hz or 60Hz (Auto-Sensing)
<b>OUTPUT</b>	
Voltage Regulation	+/- 10%
Frequency	AC mode: 47-53Hz for 50Hz or 57-63Hz for 60Hz; Battery mode: 50Hz or 60Hz +/- 1Hz
Waveform	Simulated Sinewave
Transfer Time	< 6ms(Typical)
Outlet: Schuko	3pcs with Backup/AVR/Surge protected + 3pcs Surge protected only
<b>BATTERY</b>	
Voltage	12VDC
Type	12V/9AH*1pc
Recharge Time	5 hours to 90% after complete discharge
Safety Protection	Over Charge & Over Discharge Protection
Advance Battery Management	Yes
<b>DISPLAY</b>	
LED Status Indicators	AC normal (Blue), Battery Backup (Yellow), UPS cut off / Fault (Red)
<b>AUDIBLE ALARM</b>	
Battery Mode	Two short tones every 8 seconds
Low Battery	Four short tones every seconds
Overload	Red LED: Flashing, Buzzer: Beeping continuously
Fault	Beeping continuously
<b>MANAGEMENT</b>	
USB Communication Port (Optional)	Download monitoring software can support Microsoft Windows 2000/XP/Vista/7/8/10, Microsoft Windows Server 2003/2008/2012, Novell NetWare v3.1x/v4.x/v5.x, Linux, FreeBSD, MacOSX10.5.5

ENVIRONMENT	
Operating Temperature	0° C - 40° C (32° F ~ 104° F)
Humidity	0-95% (Non-condensing)
Acoustic Noise	<40 db at 1M
PHYSICAL	
Dimension (W*D*H)	320*175*95mm

[Download Datasheet](#)

\* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/808/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email [sales@citraweb.com](mailto:sales@citraweb.com)

www.citraweb.com