

RG-RAP2200(E) Reyee Wi-Fi 5 Ceiling Access Point



Kode : RG-RAP2200(E)
Kategori : Ruijie & Reyee Wireless
Harga : Rp 852.000,00

RG-RAP2200(E) Reyee Wi-Fi 5 Indoor Ceiling with Cloud Managed Access Point.

***Belum termasuk adaptor dan poe injector**

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial

08112039555

- Dual-radio performance, up to 1.267Gbps.
- Get better performance with 802.11ac wave 2's MU-MIMO technology.
- Support to optimize the entire wireless network with just one click.
- Easily set up your Wi-Fi network with Ruijie Cloud APP in 3 minutes.
- With Ruijie Cloud, easy to maintain your networks remotely.



Specification

Model	RG-RAP2200(E)
-------	---------------

Radio	Dual-stream dual-band
Protocol	Wi-Fi 5 (IEEE 802.11ac Wave 2/Wave1) Wi-Fi 4(IEEE 802.11n) 802.11a/b/g
Operating Bands	802.11b/g/n? 2.4 GHz ~ 2.4835 GHz 802.11a/n/ac: 5 GHz: 5.150 GHz?5.350 GHz, 5.725 GHz?5.850 GHz
Antenna	Built-in Omnidirectional Antennas (2.4 GHz: 2dBi, 5 GHz: 2dBi)
Spatial Streams	2.4 GHz: 2x2 MIMO 5 GHz: 2x2 MIMO
Max Throughput	Up to 400 Mbps at 2.4 GHz Up to 867 Mbps at 5 GHz 1.267 Mbps per AP
Service Ports	2 x10/100/1000M Base-T LAN1 port supports PoE
Power Supply	802.3af/802.3at PoE, local power supply, DC 12V/1.5A (Note: The power adapter is sold as an optional accessory)
Power Consumption	≤ 12.95 W
Operating temperature	0°C?40°C
Storage temperature	-40°C?70°C
MTBF	>400000H
Operating Mode	AP mode and routing mode
Maximum number of clients	110
Recommended number of clients	40 (8 at 2.4 GHz, 32 at 5 GHz)
Maximum Number of SSIDs	8

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/937/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com