

# RG-AP720-L Wireless Access Point



**Kode** : RG-AP720-L  
**Kategori** : Ruijie & Reyee Wireless  
**Harga** : Rp 1.223.000,00

The Ruijie AP720-L is a high performance 802.11ac Wave 2 access point with 2x2 MU-MIMO and concurrent Dual-band design, data rate of up to 1.167Gbps.

**\*Belum termasuk adaptor dan poe injector**

**Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.**

Penawaran Harga Spesial

 **08112039555**

- Featuring leading 802.11 ac Wave2.
- Supports 2 spatial streams and delivers up to 300Mbps @2,4G (802.11b/g/n) and 867Mbps @5G (802.11a/n/ac).
- Dual-band performance speeds up to 1.167Gbps per device.
- Totally eliminating Gigabit wireless bottlenecks.



## Specification

<b>Model</b>	RG-AP720-L
<b>Radio</b>	Concurrent Dual-band
<b>Protocol</b>	Support concurrent 802.11b/g/n and 802.11a/n/ac

<b>Operating Bands</b>	802.11b/g/n: 2.4 GHz to 2.4835 GHz 802.11a/n/ac: 5.15 GHz to 5.35 GHz, 5.47 GHz to 5.725 GHz, 5.725 GHz to 5.85G (Depending on which country the AP is installed)
<b>Antenna</b>	Built-in antenna (2.4G : 3dBi, 5G : 3dBi)
<b>Spatial Streams</b>	2x2
<b>Max Throughput</b>	Up to 300Mbps at 2.4 GHz Up to 867Mbps at 5 GHz 1167Mbps per AP
<b>Service Ports</b>	1 x10/100/1000 Base-T Uplink supports PoE 1 Console Port
<b>Power Supply</b>	802.3af PoE, local power supply, DC 12V/1.5A (optional) (Note: The power adapter is sold as an optional accessory)
<b>Power Consumption</b>	≤ 12.95 W
<b>Operating temperature</b>	10°C to 50°C
<b>Storage temperature</b>	-40°C to 70°C
<b>MTBF</b>	>400,000H
<b>Maximum number of clients</b>	256
<b>Recommended number of clients</b>	40 (8 at 2.4 GHz, 32 at 5 GHz)
<b>Maximum Number of BSSID</b>	32

[Download Datasheet](#)

\* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

**URL :** <https://www.citraweb.com/produk/954/>

**Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email [sales@citraweb.com](mailto:sales@citraweb.com)**